

ELT ties are available with and without coating.


ELT Buckle Lock Stainless Steel Cable Ties

Features and Benefits

The ELT ties are manufactured from heavy duty, 316 grade stainless steel. Once installed they can be opened and re-used if required.

ELT Type

- ≠ 2 strap widths available
- ≠ Simple to install by hand or MTT4 tool
- ≠ Marine Grade 316 SS
- ≠ Available coated or un-coated
- ≠ Tough & corrosion resistant
- ≠ Flame retardant
- ≠ -80°C to +538°C



ELT RANGE

Part Number	Length (L)	Width (W)	Bundle Ø max.	Material	Application Tool
ELT Uncoated: SS 316					
ELT8SS5	230	5.0	60.0	SS 316	MTT4
ELT12SS5	330	5.0	90.0	SS 316	MTT4
ELT16SS5	430	5.0	120	SS 316	MTT4
ELT24SS5	630	5.0	180	SS 316	MTT4
ELT8SS10	230	10.0	60.0	SS 316	MTT4
ELT12SS10	330	10.0	90.0	SS 316	MTT4
ELT16SS10	430	10.0	120	SS 316	MTT4
ELT24SS10	630	10.0	180	SS 316	MTT4
ELT Fully Coated: SS 316					
ELT8SSC5	230	5.26	60.0	SS 316	MTT4
ELT12SSC5	330	5.26	90.0	SS 316	MTT4
ELT16SSC5	430	5.26	120	SS 316	MTT4
ELT24SSC5	630	5.26	180	SS 316	MTT4
ELT8SSC10	230	10.26	60.0	SS 316	MTT4
ELT12SSC10	330	10.26	90.0	SS 316	MTT4
ELT16SSC10	430	10.26	120	SS 316	MTT4
ELT24SSC10	630	10.26	180	SS 316	MTT4

All dimensions in mm. Subject to technical changes.

MTT4

Part Number	Suitable Ties	Pack Qty
Application Tool		
MTT4	ELT Range	1

- ≠ For use with all sizes of ELT stainless steel cable ties
- ≠ Simple ratchet operation
- ≠ Operator controlled tensioning and cutting facility
- ≠ Lightweight design and easy to use

